HSF

TECHNICAL SPECS:
Current Rating:3.0AMP
Contact Resistance:10mΩ Max
Dielectric Strength: Min 1000VRMS
Mechanical Life: Min 500 cycles
Mating Pin:ø0.40 to ø0.66mm or 0.50SQ
Forces: (polished steel gauge ø0.47mm)
Insertion:200g Max/Pin, Withdrawal:60g/Pin
Operation Temperature:-40°C to +105°C

Sleeve:Brass CuZn36Pb3(C36000),Sn over Ni
Contact Clip(4 finger):BeCu(C17200),Au or Sn over Ni
Insulator Material:PPS+30%G.F(UL94V-0)

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)





NO.of PIN	DIM A
40PIN	2.0*NO.of Positions+1.00±0.40
<40PIN	2.0*NO.of Positions $^{+0.60}_{-0.40}$

A1

Ordering Information

3522-281 XX S XX 074 X 1

- No. of Pin: 2~40PIN
- Contact Plating: S0=Gold Flash/Tin, S3=10u"Gold/Tin, S4=15u"Gold/Tin, S5=30u"Gold/Tin, SN=Tin
- Packing: A=Tray, T=Tube





Item	Pitch	Mating
Standard	2.00	3512
Alternate		

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A1	2013/05/17	Modify drawing	------
A0	2012/10/17	NEW	------

OPERATION	
X.X	±0.40
X.XX	±0.25
X.XXX	±0.15
Angle	± 3°
DIM	TOL

DRAW	Wang	DATE	2013/05/17
CHECK		DATE	
APPROVE		DATE	

SCALE	FIT
UNIT	mm
SIZE	A4
SHEET	1/1
PROJ.	

PART NO. 3522-281XXSXX074X1

TITLE: 2.00mm MACHINED FEMALE HEADER SINGLE ROW 180° H=2.80 L=7.4

Customer NO.

WCON
Http: www.wcon.com

WCON-Dongguan
Tel: +86 769 85358920
Fax: +86 769 85358915
E-mail: sales@wcon.com

WCON-Kunshan
Tel: +86 512 57468408
Fax: +86 512 57468468
E-mail: salesks@wcon.com

WCON