

HSF

TECHNICAL SPECS:


Current Rating: 1.0AMP
 Contact Resistance: 10m Ω Max
 Dielectric Strength: Min 1000Vrms
 Mechanical Life: Min 100 cycles
 Mating Pin: φ0.40 to φ0.56mm
 Forces: (polished steel gauge φ0.45mm)
 Insertion: 200g Max/Pin, Withdrawal: 60g Min/Pin
 Operation Temperature: -40°C to +105°C

Sleeve: Brass CuZn36Pb3(C36000), Sn over Ni
 Contact Clip(4 finger): BeCu(C17200), Au or Sn over Ni
 Insulator Material: PPS+30%G.F(U194V-0)
 24P~32P Insulators with center one bar
 36P~48P Insulators with center two bar

Ordering Information

7110-302 XX M XX 074 X 1

Row of Pitch No. of Pin Contact Plating Packing
 2=15.24mm See tab S0=Gold Flash/Tin T=Tube
 S3=10u"Gold/Tin S4=15u"Gold/Tin R=Tape&Reel
 S5=30u"Gold/Tin SN=Tin



Recommended P.C.B Layout(Top Side)
 (PCB BOARD TOLERANCE±0.05)

Dimensional & Ordering Information

NO. of Poles	Part No.	Dim A
24	7110-30224MXX074X1	30.48
28	7110-30228MXX074X1	35.56
32	7110-30232MXX074X1	40.64
36	7110-30236MXX074X1	45.72
40	7110-30240MXX074X1	50.80
42	7110-30242MXX074X1	53.34
48	7110-30248MXX074X1	60.96

WCON

Http: www.wcon.com

WCON-Dongguan Tel: +86 769 85358920 Fax: +86 769 85358915 E-mail: sales@wcon.com
 WCON-Kunshan Tel: +86 512 57468408 Fax: +86 512 57468468 E-mail: sales@wcon.com

OPERATION	DRAW	DATE	SCALE	FIT	PART NO.
XX	JYHuogng	2012/11/02	mm		7110-302XXMXX074X1
X.XX	CHECK	DATE	A4		TITLE: 2.54mm IC SOCKET SMT H=3.0 L=7.43 Row of Pitch 15.24mm
X.XXX	Angle	± 3°	SHEET	1/1	Customer NO.
± 0.15	APPROVE	DATE	PROJ.		
CHANGE	DIM	TOL			

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2012/11/02	NEW	